


Horizontal




With spindle-shaft

Contact arrangement	Switching function Indexing angle	Function (Pole x Position)	Order number
	shorting 36°	1 x 4	07R1423
	non-shorting 36°	1 x 4 u.	07R1424

packing unit : 50 pieces

With spindle-shaft panel mounting / waterproof IP 68 / 2bar




Contact arrangement	Switching function Indexing angle	Function (Pole x Position)	Order number
	shorting 36°	1 x 4	07R1423-30000
	non-shorting 36°	1 x 4 u.	07R1424-30000

O-Ring and nut supplied

packing unit : 50 pieces


For front panel operation / screwdriver actuation



Contact arrangement	Switching function Indexing angle	Function (Pole x Position)	Order number
	shorting 36°	1 x 4	07R4423
	non-shorting 36°	1 x 4 u.	07R4424

packing unit : 50 pieces

Vertical




With spindle-shaft

Contact arrangement	Switching function Indexing angle	Function (Pole x Position)	Order number
	shorting 36°	1 x 4	07R3423
	non-shorting 36°	1 x 4 u.	07R3424

packing unit : 50 pieces

With spindle-shaft panel mounting / waterproof IP 68 / 2bar




Contact arrangement	Switching function Indexing angle	Function (Pole x Position)	Order number
	shorting 36°	1 x 4	07R3423-30000
	non-shorting 36°	1 x 4 u.	07R3424-30000

O-Ring and nut supplied

packing unit : 50 pieces

Screwdriver actuation



Contact arrangement	Switching function Indexing angle	Function (Pole x Position)	Order number
	shorting 36°	1 x 4	07R2423
	non-shorting 36°	1 x 4 u.	07R2424

packing unit : 50 pieces

1 mm = 0.04 inch, 1 inch = 25.4 mm

Items available from stock!