RCV.	DESCRIPTION	DRW.	CHK.	APP.	DATE
A	RELEASE				

Ordering infomation:

27G3670-96D10-XXH-01

- Number of Contact
- Contact Plating
  - 01 Normal
  - 10 10μ"
  - ⋮ ⋮
- G Gold Plated
- T Tin Plated
- H Duplex Plated

RoHS Compliant

Ref. 參考圖面

SPECIFICATIONS

Current Rating:
2 Amp
Insulator resistance:
1000 Megohms Min.
Contact Resistance:
30 m ohms Min.
Dielectric withstanding:
AC 1000V/1 minute
Operating Temperature:
-55° ~ +105°C
Contact Material:
Brass
Lock Material:
Phosphor Bronze
Insulator Material:
30% Glass Filled PBT UL94V-0
Color: White
Finish:
Gold, Tin or Duplex plated
Duplex plated:
Gold plated on contact area
Tin on solder area









RECOMMENDED P.C.B. LAYOUT
TOLERANCE±0.05

成品規格圖		APP.		ANGLES	±3°	SIZE	A4
				LINEAR	0.0 ±0.38	SCALE	1.5:1
TITLE	PH2.54mm DIN Right Angle Type	CHK.			0.00±0.25	SHEET	1/1
PART NO	27G3670-96D10-XXH-01						
DRW NO	270155	DR.	KEN				
UNIT	mm(INCH) PROJECT		96.01.09				

JVE GLOBAL

RCV.	DESCRIPTION	DRW.	CHK.	APP.	DATE
A	RELEASE				
B	修正圖面尺寸	王日賜	王盛富	郭豐榮	96.05.02

Ordering infomation:

27G3676-48S10-XXH-4

- Number of Contact
- Contact Plating
  - 01 Normal
  - 10 10μ"
  - ⋮ ⋮
- G Gold Plated
- T Tin Plated
- H Duplex Plated
- Dimension 4=4.00mm

SPECIFICATIONS

Current Rating:
2 Amp
Insulator resistance:
1000 Megohms Min.
Contact Resistance:
30 m ohms Min.
Dielectric withstanding:
AC 1000V/1 minute
Operating Temperature:
-55° ~ +105°C
Contact Material:
Phosphor Bronze
Lock Material:
Phosphor Bronze
Insulator Material:
30% Glass Filled PBT UL94V-0
Color: White
Finish:
Gold, Tin or Duplex plated
Duplex plated:
Gold plated on contact area
Tin on solder area

RoHS Compliant

Ref. 參考圖面









RECOMMENDED P.C.B. LAYOUT
TOLERANCE±0.05

成品規格圖		APP.		ANGLES	±3°	SIZE	A4
				LINEAR	0.0 ±0.38	SCALE	1.5:1
TITLE	PH2.54mm DIN Straight Type	CHK.			0.00±0.25	SHEET	1/1
PART NO	27G3676-48S10-XXH-4						
DRW NO	270153	DR.	KEN 96.01.09				
UNIT	mm(INCH) PROJECT						

JVE GLOBAL

RCV.	DESCRIPTION	DRW.	CHK.	APP.	DATE
A	RELEASE				

Ordering infomation:

27G3670-48S10-XXH-4-01

- Number of Contact
- Contact Plating
  - 01 Normal
  - 10 10μ"
  - ⋮ ⋮
- G Gold Plated
- T Tin Plated
- H Duplex Plated
- Dimension 4=4.00mm

SPECIFICATIONS

Current Rating:
2 Amp
Insulator resistance:
1000 Megohms Min.
Contact Resistance:
30 m ohms Min.
Dielectric withstanding:
AC 1000V/1 minute
Operating Temperature:
-55° ~ +105°C
Contact Material:
Brass
Lock Material:
Phosphor Bronze
Insulator Material:
30% Glass Filled PBT UL94V-0
Color: White
Finish:
Gold, Tin or Duplex plated
Duplex plated:
Gold plated on contact area
Tin on solder area

RoHS Compliant

Ref. 參考圖面









RECOMMENDED P.C.B. LAYOUT
TOLERANCE±0.05

成品規格圖		APP.		ANGLES	±3°	SIZE	A4
				LINEAR	0.0 ±0.38	SCALE	1.5:1
TITLE	PH2.54mm DIN Straight Type	CHK.			0.00±0.25	SHEET	1/1
PART NO	27G3670-48S10-XXH-4-01						
DRW NO	270154	DR.	KEN 96.01.09				
UNIT	mm(INCH) PROJECT ◎ ◁						

JVE GLOBAL