PRODUCT GUIDE - MCE

- MATERIAL – Polycarbonate
- SIZE RANGE – 5 /9/14/28/42 MODULE VERSIONS IN 2 DESIGNS
- KNOCKOUTS IN TOP AND BOTTOM FACES
- FITTED WITH DIN rail & PEN TERMINAL STRIP
- MEMBRANE GLANDS INCLUDED
- IP65
- SMOKED GREY COVER ON ALL VERSIONS
- BASE COLOUR RAL 7035 GREY
- IMPACT RATING IK 08
- ACCESSORIES AVAILABLE
  WALL LUGS

USP = MODULAR COMPONENT ENCLOSURE



Materials

Material :	Polycarbonate/ABS
Colour	RAL7035
Cover Screw	Polyamide
Gasket material	Polyurethane

Temperatures

Temperature °C (short term)	-40°....120°C
Temperature °C (continuous)	-40°....80° C
Temperature °F (short term)	-40.....250°C
Temperature °F (continuous)	-40.....175°C

Ratings

Ingress Protection (EN60529)	IP65
Impact Resistance (EN62262)	IK08
Electrical Insulation	Totally Insulated
Halogen free (DIN/VDE0472, Part 815)	1
UV resistance	UL508
Flammability Rating	UL746C 5”
Glow Wire Test (IEC 695-2-9601) °C	960
NEMA Class	1, 3, 4,4X, 6, 6P,12,13

Certificates (PC)

SGS Fimko
Gost R
Germanischer Lloyd (GL)