

icotek

NEW

New Product

New Product

New Product

New Product

C^{RU} US
in progress

IP65
certified

IP66
certified

IP67
certified

IP68
certified

NEMA
TYPE
12
in progress

NEMA
TYPE
4X
in progress

HL3
EN 45545-2

ECOLAB
certified

RoHS
compliant

Made in
Germany

KVT-ER


Split cable glands



up to
IP68



Certified protection class
IP65/IP66/IP67/IP68



Slit KT grommets

1

Product description

KVT-ER are split cable glands for routing and sealing cables with connectors, with diameters from 1 to 16 mm (KT 1 - 15) and 16 to 35 mm (KT 16 - 34).

Due to the injected gasket and if single-hole grommets are used, the KVT-ER provides certified protection ratings IP65/IP66/IP67/IP68. When using multi-hole or special grommets, protection is downgraded to IP54.

The KVT-ER sizes are based on metric standard cut-outs M32, M50 and M63. Hexagonal locknuts are included in the shipment.

For assembly, we recommend to tighten the cover lid screws with max. 2 Nm.

Locknuts

Locknuts with special cut-outs are available separately.



KGM-SUB-D9 fits D-Sub 9 connectors
(Required wall cut-out: Ø 36 mm, PU: 10)
■ Order No. 45106

KGM-SUB-D25 fits SUB-D25 connectors
(Required wall cut-out: Ø 50 - 54 mm, PU: 10)
■ Order No. 45110

Description	Type	Order No.	Grommets small large	Thread Thread length	PU
	KVT-ER 32	45452	1 -	M32 x 1.5 Length: 18 mm	10
	KVT-ER 50 2	45454	2 -	M50 x 1.5 Length: 20.5 mm	5

New Product

New Product

New Product

New Product

NEW

icotek

C7US
in progress

IP65
certified

IP66
certified

IP67
certified

IP68
certified

NEMA
TYPE
12
in progress

NEMA
TYPE
4X
in progress

HL3
EN 45545-2

ECOLAB
certified

RoHS
compliant

Made in
Germany

KVT-ER

Split cable glands



Injected elastomer gasket



Slit KT grommets



up to
IP68

1

Type	Order No.	Grommets small large	Thread Thread length	PU	Description
KVT-ER 63 1	45455	- 1	M63 x 1.5 Length: 20.5 mm	5	
KVT-ER 63 4	45456	4 -	M63 x 1.5 Length: 20.5 mm	5	

Advantages & benefits

- Certified protection class IP65/IP66/IP67/IP68 according to EN 60529
- Very high strain relief according to EN 62444
- Warranty of pre-terminated cables remains
- Retrofits, repairs and maintenance can be done easily and quickly
- High cable density
- Suitable for metric cut-outs
- Hexagonal nut included in the delivery
- Very robust housing, vibration resistant
- Modern design

Specifications

Material	Material: Polypropylene (PP)
Flame class	Injected gasket: Elastomer
IP rating	UL94-Vo, self-extinguishing
Temperature	IP65/IP66/IP67/IP68, if correctly assembled with single grommets (certified acc. to EN 60529)
Properties	- 30°C to + 110°C (static)
Cut-out dimension	Halogen-free, silicone-free
	Metric sizes

Accessories

KT Cable grommets	44 - 46
KVT-EMC Brackets	129
Locknuts	170 -171
ST Plugs	49